

Colored Quartz

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture

Product Name / Trade Name RT-CQ (Colored Quartz)

CAS No. Mixture

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Industrial Flooring Filler

Uses Advised Against None

Details of the supplier of the safety data sheet

Company Identification Res-Tek, Inc.

110 Riverside Drive Cartersville, Georgia 30120 United States of America

Telephone 1-888-737-8351 / 1-770-427-4034

Emergency telephone number CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect

calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Label elements

Hazard Symbol(s)

STOT RE 1; Carc. 1A



Signal Word(s) DANGER

Hazard Statement(s)

May cause cancer.

Causes damage to organs through prolonged or repeated exposure: Lungs

Precautionary Statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust.

In case of inadequate ventilation wear respiratory protection.

Wash hands and exposed skin after use.

Do not eat, drink or smoke when using this product.

Other hazards

Particles may cause eye irritation by mechanical action.

Particles may cause skin irritation by mechanical action.

Additional Information Control dust formation.

Date: February 11, 2019 Page: 1/6



Colored Quartz

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition/information on ingredients	%W/W	CAS No.	Hazard Statement(s)
Crystalline silica (quartz) Sand and Flour	90 - 100	14808-60-7	Carc. 1A; H350 STOT RE 1; H372
2-(2-Butoxyethoxy)ethanol	<0.2	112-34-5	Acute Tox. (Oral) 5: H303
Triethoxy(ethyl)silane	<0.1	78-07-9	Acute Tox. (Oral) 5: H303

For full text of H phrases see section 16.

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing. Keep patient at

rest and give oxygen if breathing difficult. If symptoms continue, get medical

attention. Get medical advice/attention if you feel unwell.

Skin Contact Gently wash with plenty of soap and water. If irritation (redness, rash,

blistering) develops, get medical attention.

Eye Contact Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If irritation develops and persists, get

medical attention.

Ingestion Not normally required. Do not induce vomiting. Do not give anything by mouth

to an unconscious person. Get medical advice/attention if you feel unwell.

Most important symptoms and effects, both

acute and delayed

None known

Indication of any immediate medical attention

and special treatment needed

None known

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media Non-combustible. As appropriate for surrounding fire.

-Unsuitable Extinguishing Media None anticipated.

Special hazards arising from the substance or

mixture

None known

Advice for fire-fighters Fire fighters should wear complete protective clothing including self-contained

breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

emergency procedures

Avoid skin contact. Do not get in eyes. Wear protective gloves / protective

clothing / eye protection / face protection. Do not breathe dust.

Environmental precautions Do not allow to enter drains, sewers or watercourses.

Date: February 11, 2019 Page: 2/6



EPO-Colored Quartz Colored Quartz

Methods and material for containment and

cleaning up

Sweep spilled substances into containers. Moisten first to prevent dusting. Transfer to a container for disposal or recovery. Wash the spillage area with

water. Do not allow to enter drains, sewers or watercourses.

Reference to other sections

Additional Information

Inhalable size dust particles may be released under certain conditions of handling. This dust may contain crystalline silica dust which: Causes damage to

organs: Lungs (silicosis) and May cause cancer: Lungs

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Avoid skin contact. Do not get in

eyes. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust. Do not use in areas without adequate

ventilation.

Conditions for safe storage, including any incompatibilities

-Storage temperature Ambient temperatures.

-Incompatible materials None known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits

		(8hr TWA)		(STEL)		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Crystalline Silica (respirable particulate)	14808-60-7	10 mg/m³ %SiO ₂ + 2	0.025 mg/m3 ^			See below
2-(2-Butoxyethoxy)ethanol	112-34-5					
Triethoxy(ethyl)silane	78-07-9					

[^]Suspected Human Carcinogen; *Refer to OSHA 29 CFR 1910.1000 & 29 CFR 1926.55; 8hr TWA = 8 hour time-weighted average; STEL = Short Term Exposure Limit

Exposure controls

Appropriate engineering controls

Use only outdoors or in a well-ventilated area. Control dust formation.

Personal protection equipment

Eye/face protection

The following to be used as necessary: Safety Glasses



Skin protection (Hand protection/ Other)

The following to be used as necessary: Leather or thick textile gloves.





Date: February 11, 2019 Page: 3/6



Inhalable size dust particles may be released under certain conditions of handling. Respiratory protection may be needed if occupational exposure

Colored Quartz

Respiratory protection



limits are exceeded. Air-purifying respirator with particulate filter may be sufficient. Check with protective equipment manufacturer's data.

Thermal hazards Not normally required.

Environmental Exposure Controls Not normally required.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Solid.
Color. Color Varies.

Odor None to slight butyl odor.

Odor Threshold (ppm)

Not available.

pH (Value)

Not applicable.

Melting Point (°C) / Freezing Point (°C)

1,610 (2,930 °F)

Boiling point/boiling range (°C):

Flash Point (°C)

Flash Point (°C)

Evaporation Rate

Flammability (solid, gas)

Explosive Limit Ranges

Vapor pressure (Pascal)

Vapor Density (Air=1)

Not available.

Non-combustible

Non-combustible

Non-combustible

Non-combustible

Not applicable.

Density (g/ml) 2.65 (22-12 lbs./gallon)

Specific Gravity

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

2.65

Insoluble

Not known

Not applicable.

Auto Ignition Point (°C)

Decomposition Temperature (°C)

Kinematic Viscosity (cSt) @ 40°C

Evaluation Coefficient (n-Octanol/water)

Not applicable.

Not available.

Not applicable.

Explosive properties Not explosive.
Oxidizing properties Not oxidizing.

Other information Not available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

 Chemical stability
 Stable.

 Possibility of hazardous reactions
 None known.

 Conditions to avoid
 None known.

Incompatible materials Strong oxidizing agents such as fluorine, chlorine trifluoride, manganese

trioxide, and oxygen difluoride, may cause fire.

Hazardous decomposition product(s)

Silica will dissolve in hydrofluoric acid producing a corrosive gas, silicon

tetrafluoride.

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Crystalline Silica (CAS# 614808-60-7):

Acute toxicity LD50 (rat): >5000 mg/kg bw

LD50 (dermal): >2000 mg/kg bw

LC50 (inhalation, fume): >94.4 mg/m³ - Causes damage to organs: Lungs (silicosis)

Irritation/Corrosivity Not to be expected

Date: February 11, 2019 Page: 4/6



Colored Quartz

Sensitization Not to be expected

Repeated dose toxicity Causes damage to organs through prolonged or repeated exposure: Lungs (silicosis)

Carcinogenicity May cause cancer. Lungs

NTP	IARC	ACGIH	OSHA
Yes.	Group 1	A2	Yes.

Group 1 = Carcinogenic to humans. A2 = Suspected Human Carcinogen. When present as respirable particles

Mutagenicity Not to be expected. Reproductive toxicity Not to be expected.

2-(2-Butoxyethoxy) ethanol (CAS# 112-34-5)

Acute toxicity LD50 (Oral, rat): 7291 mg/kg bw

LD50 (Dermal, rabbit): 2,764 mg/kg bw

Triethoxy(ethyl)silane (CAS# 78-07-9)

Acute toxicity LD50 (Oral, rat): 14,000 mg/kg bw

LD50 (Dermal, rabbit): 14,320 mg/kg bw

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity This product is not expected to present an environmental hazard.

Crystalline Silica (CAS# 614808-60-7): LC50 (72 hr): >10,000 mg/L (Carp)

LL50 (48 hour): 0.8 mg/l (Fish)

LL50 (48 hour): 202 µg/L (Aquatic Invertebrates)

Long Term No data

Persistence and degradability Readily biodegradable

The whole fish BCF was found to be 1,850 Bioaccumulative potential Mobility in soil The product has low mobility in soil. Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

2-(2-Butoxyethoxy) ethanol (CAS# 112-34-5) LC50 (96 hr) 1,300 mg/L (Lepomis macrochirus, Bluegill sunfish)

Triethoxy(ethyl)silane (CAS# 78-07-9) No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national legislation.

Consult an accredited waste disposal contractor or the local authority for

advice.

Additional Information None known.

SECTION 14: TRANSPORT INFORMATION

Land transport Sea transport Air transport (U.S. DOT) (IMDG) (ICAO/IATA)

Not classified as dangerous for transport.

UN number

Proper Shipping Name Transport hazard class(es)

Packing group

Environmental hazards

Special precautions for user

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

Date: February 11, 2019 Page: 5/6



Colored Quartz

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None			

SARA 311/312 - Hazard Categories: None

☐ Fire ☐ Sudden Release ☐ Reactivity ☐ Immediate (acute) ☐ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
2-(2-Butoxyethoxy) ethanol	112-34-5	<0.2

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

Proposition 65 (California):

Chemical Name	CAS No.	Typical %wt.	Hazards
Crystalline Silica	14808-60-7	98 - 99	Cancer

WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1 - 16.

Date of preparation: February 11, 2019

Hazard Statement(s) Listed in: SECTION 3

H303: May be harmful if swallowed.

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

Additional Information: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Date: February 11, 2019 Page: 6/6