

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name
Product Name / Trade Name
CAS No.

Mixture
MAC-Guard™ MAC-925 Topcoat
Mixture

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)
Uses Advised Against

Industrial Flooring Resin
None

Details of the supplier of the safety data sheet

Company Identification

Res-Tek, Inc.
110 Riverside Drive
Cartersville, Georgia 30120
United States of America
1-888-737-8351 / 1-770-427-4034

Telephone

Emergency telephone number

CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Liq. 2; Skin Irrit. 2; Eye Irrit. 2; Skin Sens. 1; STOT SE 3

Label elements

Hazard Symbol



Signal Word(s)

DANGER

Hazard Statement(s)

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
Take precautionary measures against static discharge.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Use explosion-proof electrical/ventilating/lighting/equipment.
Keep container tightly closed.
Wear protective gloves/eye protection/face protection.
Do not breathe dust/fume/gas/mist/vapours/spray.

Do not eat, drink or smoke when using this product.

Wash hands and exposed skin after use.

Contaminated work clothing should not be allowed out of the workplace.

Other hazards

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Additional Information

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Composition/information on ingredients	%W/W	CAS No.	Hazard Statement(s)
Methyl methacrylate	60 - 80	80-62-6	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335
Proprietary acrylic polymer	10 - 25	Trade Secret	Not classified as dangerous for supply/use.
Proprietary methacrylic acid ester	2 - 10	Trade Secret	Skin Sens. 1B; H317 Aquatic Acute 3; H402
Proprietary substituted tertiary amine	1 - 4	Trade Secret	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 Aquatic Acute 3; H402

For full text of H phrases see section 16.

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is labored, administer oxygen. If symptoms persist, obtain medical attention.

Skin Contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If irritation (redness, rash, blistering) develops, get medical attention. Wash contaminated clothing before reuse.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Get medical advice/attention if you feel unwell. Treat symptomatically.

Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

None anticipated.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media

Extinguish with water spray, dry chemical, sand or carbon dioxide.

-Unsuitable Extinguishing Media

None anticipated.

Special hazards arising from the substance or mixture

None anticipated.

Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Put on protective equipment before entering danger area. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Environmental precautions

Contain spillages with sand, earth or any suitable adsorbent material. Do not allow to enter drains, sewers or watercourses.

Methods and material for containment and cleaning up

Contain spillages with sand, earth or any suitable adsorbent material. Transfer to a container for disposal or recovery. Wash the spillage area with water. If possible prevent water running into sewers.

Reference to other sections
Additional Information

None
None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof electrical / ventilating / lighting / equipment. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands and exposed skin after use. Do not breathe dust / fume / gas / mist / vapors / spray. Contaminated work clothing should not be allowed out of the workplace. Work in well ventilated zones or use proper respiratory protection.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Store at room temperature. Keep container tightly closed and in a well-ventilated place. Keep away from heat and sources of ignition.

-Incompatible materials

Strong oxidising agents and amines.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Methyl methacrylate	80-62-6	100 ppm	50 ppm	-----	100 ppm	-----
2,6-di-tert-butyl-p-cresol	128-37-0	-----	2 mg/m3	-----	-----	IFV

- STEL: Short Term Exposure Limit; IFV = Inhalable Fraction & Vapor

Exposure controls

Appropriate engineering controls

Work in well ventilated zones or use proper respiratory protection.

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Gloves (Butyl rubber). Check with protective equipment manufacturer's data. Gloves should be changed regularly to avoid permeation problems.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Air-purifying respirator with organic vapor cartridges may provide sufficient protection. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required.

Environmental Exposure Controls

Do not allow to enter drains, sewers or watercourses.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid
Color.	Blue / Bluish
Odor	Sweet Ester-like
Odor Threshold (ppm)	Not available.
pH (Value)	Not available.
Melting Point (°C) / Freezing Point (°C)	- 48 (-54 °F)
Boiling point/boiling range (°C):	100 (212 °F)
Flash Point (°C)	9 (48°F)
Evaporation Rate	> 1 (Butyl acetate = 1)
Flammability (solid, gas)	Not applicable.
Explosive Limit Ranges	Not available.
Vapour pressure (mmHg)	37.8 @ 20°C
Vapour Density (Air=1)	Not available
Density (g/ml)	0.98 @ 20 °C (8.16 lb/gal @ 20 °C)
Specific Gravity	0.97
Solubility (Water)	Not available.
Solubility (Other)	Not available.
Partition Coefficient (n-Octanol/water)	Not available.
Auto Ignition Point (°C)	430 (806°F)
Decomposition Temperature (°C)	Not available.
Kinematic Viscosity (cSt)	> 20.5 @ 20 °C (21 Sec. No. 4 ISO Beaker)
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

Other information

VOC Content: less than 100g/l

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions.

Chemical stability

Stable.

Possibility of hazardous reactions

Not to be expected.

Conditions to avoid

Incompatible materials.

Incompatible materials

Strong oxidising agents and amines.

Hazardous decomposition product(s)

Combustion or thermal decomposition will evolve toxic and irritant

vapours; acrid smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Acute toxicity (estimated / calculated)

Oral: LD50: > 2000 mg/kg (rat)

Dermal: LD50: > 2000 mg/kg (rat)

Corrosivity / Irritation

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Sensitization

May cause sensitization by skin contact.

Repeated dose toxicity

Not to be expected.

Mutagenicity

Not to be expected.

Carcinogenicity

Not to be expected.

NTP	IARC	ACGIH	OSHA
No.	No.	No.	No.

Toxicity for reproduction

Not to be expected.

Other information

None known.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity (estimated / calculated)

Acute toxicity

LC50 (96 hour): < 1 mg/l (Fish)

EC50 (48 hour): <1 mg/l (Daphnia magna)

Long Term Toxicity

EC50 (48 hour): <1 mg/l (Daphnia magna)

Persistence and degradability

Not readily biodegradable.

Bioaccumulative potential

The product has no potential for bioaccumulation.

Mobility in soil

The product has low mobility in soil.

Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

Additional Information

None known.

SECTION 14: TRANSPORT INFORMATION

	Land transport (U.S. DOT)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	UN 1866	UN 1866	UN 1866
Proper Shipping Name	Resin Solution	Resin Solution	Resin Solution
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	Yes *	No	No
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

* Reportable Quantity (RQ) substance

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Methyl methacrylate	80-62-6	50 - 60	1000

SARA 311/312 - Hazard Categories:

☒ Fire ☐ Sudden Release ☐ Reactivity ☒ Immediate (acute) ☒ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Methyl methacrylate	80-62-6	50 - 60

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)	TPQ (Pounds)
None	-----	-----	-----	-----

Proposition 65 (California):

Chemical Name	CAS No.	Typical %wt.	Hazards
None	-----	-----	-----

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1.

Date of preparation: April 24, 2018

Hazard Statement(s) Listed in: SECTION 3

H225: Highly flammable liquid and vapor.
H226: Flammable liquid and vapour.
H227: Combustible liquid.
H302: Harmful if swallowed.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H402: Harmful to aquatic life.

Additional Information: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.