

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product Name: EPO-Guard™ EPO-202 Part B
Revision Date: Oct 09, 2025 **Date Printed:** Oct 09, 2025
Version: 1.0 **Supersedes Date:** N.A.
Manufacturer's Name: APN Res-Tek, LLC
Address: 110 Riverside Drive SW Cartersville, GA, 30120 United States of America
Emergency Phone: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted).
Information Phone Number: 1-888-737-8351 / 1-770-427-4034
Product/Recommended Uses: Industrial Flooring Resin

SECTION 2) HAZARDS IDENTIFICATION

Classification

Serious Eye Damage - Category 1
Skin Corrosion - Category 1B
Skin Sensitizer - Category 1
Chronic aquatic toxicity - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Health

H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction

Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection/face protection.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.

Precautionary Statements - Response

- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 - Immediately call a POISON CENTER or doctor.
- P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P363 - Wash contaminated clothing before reuse.
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P321 - Specific treatment (see First-Aid on this label).
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.

Precautionary Statements - Storage

- P405 - Store locked up.

Precautionary Statements - Disposal

- P501 - Dispose of contents/container in accordance with local/national/international regulations.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0038294-64-3	REACTION PRODUCTS OF 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE AND 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3EPOXYPROPANE	40% - 50%
0000100-51-6	BENZYL ALCOHOL.	40% - 50%
0002855-13-2	ISOPHORONE DIAMINE	10% - 20%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 30 minutes or until medical aid is available. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor. Avoid direct contact. Wear chemical protective gloves, if necessary.

Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Rinse skin with lukewarm, gently flowing water/shower for a duration of 30 minutes or until medical aid is available. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before re-use or discard.

Ingestion

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire: Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards Arising from the Chemical

Runoff may pollute waterways Fire will produce irritating and corrosive gases.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Evacuate and isolate hazard area and keep unauthorized personnel away.

Protective Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Wear liquid tight chemical protective clothing in combination with positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Avoid breathing vapor or mist. Do not get on skin, eyes or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Ventilate area after clean-up is complete.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. All containers must be properly labelled. Do not get in eyes, on skin, or on clothing. Eyewash stations and showers should be available in areas where this material is used and stored Do not breathe vapor or mist.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

None of the chemicals in Section 3 are regulated under "ACGIH_carcinogen", "ACGIH_Notations", "ACGIH_TLV_Basis", "ACGIHsmg - ACGIH_STEL_(mg/m3)", "ACGIHsppm - ACGIH_STEL_ppm", "ACGIHtmg", "ACGIHtppm", "CAN_AL_Carcinogen", "CAN_AL_Notation", "CAN_ALsmg", "CAN_ALsppm", "CAN_ALtmg", "CAN_ALtppm", "CAN_ONsmg", "CAN_ONsppm", "CAN_ONtmg", "CAN_ONtppm", "CAN_QCVECDmg - CANADA_QUEBEC VALEUR D'EXPOSITION DE COURTE DURÉE_mg", "CAN_QCVECDppm - CANADA_QUEBEC VALEUR D'EXPOSITION DE COURTE DURÉE_ppm", "CAN_QCVEMPmg - CANADA_QUEBEC VALEUR D'EXPOSITION MOYENNE PONDÉRÉE_mg", "CAN_QCVEMPppm - CANADA_QUEBEC VALEUR D'EXPOSITION MOYENNE PONDÉRÉE_ppm", "CANsmg", "CANsppm", "CANTmg", "CANTppm", "NIOSH_carcinogen", "nioshsmg", "nioshsppm", "nioshtmg", "nioshtppm", "OSHA_SkinDesignation", "OSHA_Tables_Z1_Z2_Z3", "OSHA_Carcinogen - OSHA Carcinogen", "OSHAsmg", "OSHAsppm", "OSHAtmg", "OSHAtppm"

ppSECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid Dispersion.
Color.	Amber.
Odor	Amine like.
Odor Threshold (ppm)	Not available.
pH (Value)	Not available.
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	205 - 247(401 - 476°F).
Flash Point (°C)	Not available.
Evaporation Rate	Not available.
Flammability (solid, gas)	Not applicable.
Explosive Limit Ranges	Not available.
Vapour pressure (mmHg)	Not available.
Vapour Density (Air=1)	Not available.
Density (g/ml)	1.026 @ 25 °C (8.56 lb/gal).
Specific Gravity	1.026
Solubility (Water)	Not available.
Solubility (Other)	Not available.
Partition Coefficient (n-Octanol/water)	Not available.
Auto Ignition Point (°C)	Not available.
Decomposition Temperature (°C)	Not available.
Dynamic Viscosity (cPs @ 25°C)	65.
Explosive properties	Not available.
Oxidizing properties	Not available.
Other information	VOC Content: 419.57 g/L less water.

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid heat, sparks, flame, high temperature and contact with incompatible materials.

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

The Acute Toxicity Estimate (ATE) for an inhalation (dust and mist) exposure to this mixture is >5 mg/l

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

May cause an allergic skin reaction

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

Causes serious eye damage

0000100-51-6 BENZYL ALCOHOL

Contact with eyes causes local irritation.

Skin Corrosion/Irritation

Causes severe skin burns and eye damage

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000100-51-6 BENZYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

Chronic Exposure

Based on available data, the classification criteria are not met.

Potential Health Effects - Miscellaneous

Based on available data, the classification criteria are not met.

Miscellaneous Health Effects

0000100-51-6 BENZYL ALCOHOL

Inhalation of vapor may cause irritation of upper respiratory tract. Prolonged or excessive inhalation may result in headache, nausea, vomiting, and diarrhea. In severe cases, respiratory stimulation followed by respiratory and muscular paralysis, convulsions, narcosis and death may result. Ingestion may produce severe irritation of the gastrointestinal tract, followed by nausea, vomiting, cramps and diarrhea; tissue ulceration may result.

0000100-51-6 BENZYL ALCOHOL

LC50(Inhalation, rat):>500 mg/m³; Toxic effects: Behavioral - somnolence (general depressed activity) Behavioral - ataxia Lungs, Thorax, or Respiration - respiratory depression; Reference: VCVGK* "Vrednie chemicheskije veshestva, galogen I kislород sodergashie organicheskie soedinenia". (Hazardous substances. Halogen and oxygen containing substances), Bandman A.L. et al., Chimia, 1994. Volume (issue)/page/year: -,132,1984

LD50(Dermal, rabbit): 2000 mg/kg; VCVGK* "Vrednie chemicheskije veshstva, galogen I kislород sodergashie organicheskie soedinenia". (Hazardous substances. Halogen and oxygen containing substances), Bandman A.L. et al., Chimia, 1994. Volume (issue)/page/year: -, 132, 1984

LD50(Oral, rat): 1230 mg/kg; Toxic effects: Behavioral - somnolence (general depressed activity) Behavioral - excitement Behavioral - coma

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

Persistence and Degradability 0000100-51-

6 BENZYL ALCOHOL Readily biodegradable.

Bioaccumulative Potential

0000100-51-6 BENZYL ALCOHOL
No potential for bioaccumulation.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000100-51-6 BENZYL ALCOHOL The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

Display Order	U.S. DOT Information	IMDG Information	IATA Information
UN Number:	UN2735	UN2735	UN2735
UN proper shipping name:	Polyamines, liquid, corrosive, n.o.s. (ISOPHORONE DIAMINE)	Polyamines, liquid, corrosive, n.o.s. (ISOPHORONE DIAMINE)	Polyamines, liquid, corrosive, n.o.s. (ISOPHORONE DIAMINE)
Transport Hazard class(es)	8	8	8
Packing group	III	III	III
Hazardous substance (RQ)	No Data Available	No Data Available	No Data Available
Environmental hazards	No Data Available	No Data Available	No Data Available
Special precautions for user	No Data Available	No Data Available	No Data Available
Transport in bulk according to Annex II of MARPOL and the IBC code	No Data Available	No Data Available	No Data Available

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0038294-64-3	REACTION PRODUCTS OF 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE AND 4,4'-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE	40% - 50%	DSL - Domestic Substance List, SARA312
0000100-51-6	BENZYL ALCOHOL	40% - 50%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), PA_HAZ - Pennsylvania Hazardous Substance List, Canada_ON_419, TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS
0002855-13-2	ISOPHORONE DIAMINE	10% - 20%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), NJ_RightToKnow_SpecialHealthHazard_SubList - New Jersey Right To Know Special Health Hazard Substance List, TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS

SECTION 16) OTHER INFORMATION**Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.